





Electronic Shelf Labelling solution provides easily expandable environment to retail market



### SPECIFICATIONS

Model ESL Gateway		REGX-XOXXA
Size		ø161 x 63.8 mm - Except Spring & Bracket (Slot Type Back Cover Size : ø136 x 47.8 mm)
Weight		302.5 g±10% (Except Bracket)
Operating Environment		<ul style="list-style-type: none"> <li>▶ CPU : Cortex-A9 (1GHz)</li> <li>▶ Memory : eMMC 4GB, DDR3 SDRAM 1GB</li> <li>▶ Fully integrated Antenna supported</li> <li>▶ Host USB supported for SW Upgrading</li> <li>▶ OS : Linux Kernel 3.0.35</li> <li>▶ Network &amp; maintenance function:               <ul style="list-style-type: none"> <li>• Network setup / management</li> <li>• Software upgrade</li> </ul> </li> <li>▶ On ceiling using bracket or spring</li> </ul>
Network	802.15.4 / ZigBee	2.4GHz IEEE802.15.4 compliant RF Transceiver
	WLAN	IEEE802.11b/g/n (2.4GHz)
	Ethernet	10/100 Base-T / PoE Supported
	Security	Robust wireless network (LGIT own protocol)
	Protocol	Compatible with LGIT protocol communication devices
	Comm. Range	Max. 30m (under LOS) *
	Device number	IEEE 802.15.4 RF Devices : Max. 2,000ea WLAN Devices : Max. 3ea
Operating Environment Temperature		Min 0°C; Typ 25°C; Max: 60°C
Power Rating		12V --- 1000mA (Adaptor)
Certificate of Compliance		<b>RoHS</b>   <b>CE2200</b>

\*LoS (Line of Sight) : Without any sort of an obstacle between a gateway and end devices

### TECNICAL DRAWINGS

